









































Profilübersicht und statische Profilwerte Serie Lambda 77 L Profile overview and static profile values for Series Lambda 77 L

	Profil-Nr. Profile number	I_{xid} (cm ⁴)					Abw. außen ohne Dämmzone External perimeter excluding insulating zone	Seite 77 L Page 77 L		Profil-Nr. Profile number	I_{xid} (cm ⁴)					Abw. außen ohne Dämmzone External perimeter excluding insulating zone	Seite 77 L Page 77 L
		Stützweite L (cm) nach IFBT-Richtlinie Distance between supports L(cm) in compliance with the guideline issued by the Institute of Building Technology	ab from L(cm) < 200	ab from >=200	ab from >250	ab from > 300					ab from > 400	Stützweite L (cm) nach IFBT-Richtlinie Distance between supports L(cm) in compliance with the guideline issued by the Institute of Building Technology	ab from L(cm) < 200	ab from >=200	ab from >250		
	B 803030	24	31	35	38	42	362	11		B 805220	-	-	-	-	-	416	14
	B 805010	-	-	-	-	-	329	11		B 805230	-	-	-	-	-	411	14
	B 805020	-	-	-	-	-	334	11		B 805600	-	-	-	-	-	320	15
	B 805030	-	-	-	-	-	357	12		B 805610	-	-	-	-	-	325	15
	B 805040	-	-	-	-	-	396	12		B 805620	-	-	-	-	-	257	15
	B 805200	-	-	-	-	-	397	13		B 805630	-	-	-	-	-	266	15
	B 805210	-	-	-	-	-	392	13		P 805650	-	-	-	-	-	112	16

I_{xid} = ideelles Trägheitsmoment
 I_{xid} = effective moment of inertia

I_{xid} = ideelles Trägheitsmoment
 I_{xid} = effective moment of inertia

Profilübersicht und statische Profilwerte Serie Lambda 77 L Profile overview and static profile values for Series Lambda 77 L

	Profil-Nr. Profile number	I_{xid} (cm ⁴)					Abw. außen ohne Dämmzone External perimeter excluding insulating zone	Seite 77 L Page 77 L		Profil-Nr. Profile number	I_{xid} (cm ⁴)					Abw. außen ohne Dämmzone External perimeter excluding insulating zone	Seite 77 L Page 77 L
		L(cm) < 200	Stützweite L (cm) nach IfBT-Richtlinie Distance between supports L(cm) in compliance with the guideline issued by the Institute of Building Technology								L(cm) < 200	Stützweite L (cm) nach IfBT-Richtlinie Distance between supports L(cm) in compliance with the guideline issued by the Institute of Building Technology					
		ab from ≥200	ab from >250	ab from >300	ab from >400					ab from ≥200	ab from >250	ab from >300	ab from >400				
	B 805500	-	-	-	-	545	16		B 805640	-	-	-	-	125	17		
	B 803140	38	50	61	69	82	16		B 805660	-	-	-	-	228	17		
	B 805680	-	-	-	-	200	18		B 805670	-	-	-	-	191	17		
	B 805700	-	-	-	-	229	18		P 805740	-	-	-	-	224	17		
	B 805710	-	-	-	-	220	18		P 494200	-	-	-	-	119	27		
	B 805720	-	-	-	-	332	18		P 494201	-	-	-	-	134	27		
	B 805690	-	-	-	-	148	19		P 494202	-	-	-	-	140	27		
	P 805730	-	-	-	-	153	19		P 494203	-	-	-	-	148	27		
									P 494204	-	-	-	-	154	27		
									P 594205	-	-	-	-	148	27		
									P 594206	-	-	-	-	148	27		
									P 594210	-	-	-	-	148	27		
									P 594211	-	-	-	-	148	27		
									P 594207	-	-	-	-	154	27		

I_{xid} = ideales Trägheitsmoment
 I_{xid} = effective moment of inertia

I_{xid} = ideales Trägheitsmoment
 I_{xid} = effective moment of inertia

Verglasung
Glazing

010000170