























Profilübersicht und statische Profilwerte Serie Lambda 65 M IF Profile overview and static profile values for Series Lambda 65 M IF

	Profil-Nr. Profile number	I_{xid} (cm ⁴)					Abw. außen ohne Dämmzone External perimeter excluding insulating zone	Seite Page		Profil-Nr. Profile number	I_{xid} (cm ⁴)					Abw. außen ohne Dämmzone External perimeter excluding insulating zone	Seite Page		
		L(cm)	Stützweite L (cm) nach IBT-Richtlinie Distance between supports L(cm) in compliance with the guideline issued by the Institute of Building Technology								L(cm)	L(cm)	Stützweite L (cm) nach IBT-Richtlinie Distance between supports L(cm) in compliance with the guideline issued by the Institute of Building Technology					L(cm)	
			< 200	ab from ≥200	ab from >250	ab from > 300							ab from > 400	< 200	ab from ≥200				ab from >250
	B 807020	14	16	18	19	20	338	6		B 807200	-	-	-	-	-	292	10		
	B 807030	16	19	21	22	24	372	6		B 807210	-	-	-	-	-	293	10		
	B 807000	-	-	-	-	-	339	7		B 807230	-	-	-	-	-	319	11		
	B 807010	-	-	-	-	-	339	7		P 804710	-	-	-	-	-	48	15		
	B 807010	-	-	-	-	-	339	7		P 804711	-	-	-	-	-	55	15		
	B 807300	19	23	25	27	29	471	9		P 494200	-	-	-	-	-	119	16		
	B 807310	17	21	23	25	27	474	9		P 494201	-	-	-	-	-	134	16		
	P 803712	-	-	-	-	-	63	8		P 494202	-	-	-	-	-	140	16		
	P 806713	-	-	-	-	-	118	8		P 494203	-	-	-	-	-	148	16		
										P 494204	-	-	-	-	-	154	16		
										P 804701	-	-	-	-	-	158	16		

I_{xid} = ideelles Trägheitsmoment
 I_{xid} = effective moment of inertia

I_{xid} = ideelles Trägheitsmoment
 I_{xid} = effective moment of inertia

005000100