





























Profilübersicht und statische Profilwerte Serie Lambda 77 L IF Profile overview and static profile values for Series Lambda 77 L IF

	Profil-Nr. Profile number	I_{xid} (cm ⁴)					Abw. außen ohne Dämmzone External perimeter excluding insulating zone	Seite Page		Profil-Nr. Profile number	I_{xid} (cm ⁴)					Abw. außen ohne Dämmzone External perimeter excluding insulating zone	Seite Page
		L(cm)	Stützweite L (cm) nach IBT-Richtlinie Distance between supports L(cm) in compliance with the guideline issued by the Institute of Building Technology								L(cm)	Stützweite L (cm) nach IBT-Richtlinie Distance between supports L(cm) in compliance with the guideline issued by the Institute of Building Technology					
			< 200	ab from ≥200	ab from >250	ab from > 300						ab from > 400	< 200	ab from ≥200	ab from >250		
	B 804020	21	26	30	32	35	372	9		B 804200	-	-	-	-	-	292	14
	B 804030	24	31	36	39	43	471	9		B 804210	-	-	-	-	-	292	14
	B 804000	18	21	24	26	27	306	10		B 804220	-	-	-	-	-	293	14
	B 804010	18	22	24	26	28	338	10		B 804230	-	-	-	-	-	319	15
	B 804300	23	29	33	36	40	474	12		B 804240	-	-	-	-	-	319	15
	B 804310	22	27	31	34	37	417	12									
	B 804320	34	46	55	62	73	586	13									
	P 803712	-	-	-	-	-	63	11									
	P 803713	-	-	-	-	-	118	11									

I_{xid} = ideelles Trägheitsmoment
 I_{xid} = effective moment of inertia

I_{xid} = ideelles Trägheitsmoment
 I_{xid} = effective moment of inertia

Profilübersicht und statische Profilwerte Serie Lambda 77 L IF Profile overview and static profile values for Series Lambda 77 L IF

	Profil-Nr. Profile number	I_{xid} (cm ⁴)					Abw. außen ohne Dämmzone External perimeter excluding insulating zone	Seite Page		Profil-Nr. Profile number	I_{xid} (cm ⁴)					Abw. außen ohne Dämmzone External perimeter excluding insulating zone	Seite Page
		L(cm)	Stützweite L (cm) nach IFT-Richtlinie Distance between supports L(cm) in compliance with the guideline issued by the Institute of Building Technology														
			ab from < 200	ab from ≥200	ab from >250	ab from > 300					ab from > 400	L(cm)	Stützweite L (cm) nach IFT-Richtlinie Distance between supports L(cm) in compliance with the guideline issued by the Institute of Building Technology				
	B 804320	34	46	55	62	73	586	14		P 494200	-		-	-	-	-	119
	B 804600	-	-	-	-	-	386	17		P 494201	-	-	-	-	-	134	20
	P 803712	-	-	-	-	-	63	12		P 494202	-	-	-	-	-	140	20
	P 803713	-	-	-	-	-	118	12		P 494203	-	-	-	-	-	148	20
	P 803715	-	-	-	-	-	96	12		P 494204	-	-	-	-	-	154	20
	P 804701	-	-	-	-	-	158	20		P 594205	-	-	-	-	-	148	20
	P 804710	-	-	-	-	-	48	16, 18		P 594206	-	-	-	-	-	148	20
	P 804711	-	-	-	-	-	55	17		P 594210	-	-	-	-	-	148	20
	P 494300	-	-	-	-	-	159	20		P 594100	-	-	-	-	-	91	21
	P 494301	-	-	-	-	-	163	20		P 594101	-	-	-	-	-	89	21
	P 494302	-	-	-	-	-	169	20		P 594102	-	-	-	-	-	93	21
	P 494303	-	-	-	-	-	183	20		P 594103	-	-	-	-	-	103	21
										P 594104	-	-	-	-	-	111	21
										P 594105	-	-	-	-	-	117	21

I_{xid} = ideelles Trägheitsmoment
 I_{xid} = effective moment of inertia

I_{xid} = ideelles Trägheitsmoment
 I_{xid} = effective moment of inertia

009002001