



















Accessories for porch-constructions	Door-Series			Accessories for porch-constructions	Door-Series		
	1.0	1.0 IF	A 72		1.0	1.0 IF	A 72
 <p>Z 904 819 Glazing gasket, compatible with plexiglass, with 4 mm spacer, for upper sealing level and lower timber lining</p>			•				•
 <p>Z 901 295 Glazing gasket -external-compatible with plexiglass, for profiles such as P 572 110 and P 572 301</p>			•				•
 <p>Z 901 297 Glazing gasket -internal-compatible with plexiglass, suitable for external gaskets Z 904 819 and Z 901 295, gap dimension 3,5 - 5 mm</p>			•	  <p>Z 903 233 Mandrel for driving in tapered pins and clamping sleeves</p> <p>Z 911 187 Mandrel for driving in cylindrical pins Ø 2.5 mm</p>			•
<p>Z 901 298 Glazing gasket -internal-compatible with plexiglass, suitable for external gaskets Z 904 819 and Z 901 295, gap dimension 5 - 7 mm</p>			•	 <p>Z 903 451 Screw, DIN 7982 - St 3.9 x 38 for retainer Z 904 899 2 each required</p>			•
 <p>Z 911 930 Pressure plate glazing gasket - external-black, suitable for profile P 423 401 (blue colour strip)</p>			•	 <p>Z 900 920 Screw, DIN 7982 - St 3.9 x 13</p>			•
<p>Z 906 824 Sealing tape, 15 x 2 mm, self-adhesive, glue between the gasket joints for sealing, Length = 30 m (roll) processing temperature 5 - 45°C</p>			•	 <p>Z 900 235 Screw, DIN 7981 - St 3.9 x 16</p>			•
 <p>Z 906 791 * Z 906 791 02 Z 906 791 64 Aluminium profile water channel</p>			•	 <p>Z 903 247 Screw, DIN 7981 - St 3.9 x 10</p>			•
 <p>Z 904 899 Retainer for water channel Z 906 791</p>			•	 <p>Z 900 467 Screw, DIN 7981 - St 4.8 x 19</p>			•
 <p>Z 905 965 Water channel connecting piece ø = 50 mm, for attaching a chain for water drainage</p>			•	 <p>Z 900 883 Screw, DIN 7982 - ST 4.8 x 50</p>			•
				 <p>Z 900 885 Screw, DIN 7972 - ST 4.8 x 70 thread length 50 mm</p>			•
				 <p>Z 907 796 Façade screw DIN 6901 - ST 4.8 x 50 for connection of profiles P 460 401 and P 572 702</p>			•
				 <p>Z 902 198 Rivet, flat head for drill diam. 3.1 mm, clamping range 3.5 - 4.5 mm</p>			•