HUECK
HARTMANN

Fittings and accessories for doors opening in and out
Processing and assembling drawing: Register 700

	Door-Series		
	1.0	RSC without RS	A 72
Z 904 269 Electric door opener, without unlocking, FaFix , 6 - 12 Volt DC, AC, suitable for left and right	•	•	•
Z 904 286 Electric door opener, with mechanical unlocking of electric opener latch during daytime, FaFix, 6 - 12 Volt DC, AC, suitable for left and right	•	•	•

	Door-Series		
	1.0	RSC without RS	A 72
Z 912 340 Electric door opener, with radius latch, without unlocking, FaFix, 6 - 12 Volt DC, AC, suitable for left and right	•	•	•
Z 904 341 Electric door opener, with radius latch, with mechanical unlocking of electric opener latch during daytime, FaFix, 6 - 12 Volt DC, AC, suitable for left and right	•	•	•

Special design electric openers upon enquiry!

FaFix = Door opener with adjustable and lockable door opener latch
DC = Direct current
AC = Alternating current



Z 904 290 Adjustable striking plate insert piece, designated for electric door opener	•	•	•





Z 911 160 Safety profile cylinder, 30 / 55 mm matt nickel, protected against drilling, with 3 keys	•		
Z 912 811 Safety profile cylinder, 30 / 50 mm matt nickel, with 3 keys	•		



Z 913 033 Safety profile cylinder, 45 / 45 mm matt nickel, with 3 keys		•	



Z 900 037 Safety profile cylinder, 30 / 30 mm matt nickel, protected against drilling, with 3 keys			•