Fittings and accessories for doors opening in and out
Processing and assembling drawing: Register 700

		Door-Series 1.0	RSC without RS	A 72
	**P 599 001** Push bar, aluminium square tube, 100 x 18 mm Stock length = 5 m	•	•	•
 	**Z 902 134 00** Support for push bar, height = 30 mm, suitable for P 599 001	•	•	•
 	**Z 902 126 00** Support for push bar, height = 50 mm, suitable for P 599 001	•	•	•
 	**Z 902 130 00** Support for push bar, height = 65 mm, suitable for P 599 001	•	•	•
	**Z 908 355** Adhesive tape, adhesive on both sides, 19 x 1.1 mm (3M Type 4939F) required for gluing push bar P 599 001	•	•	•
	Z 908 394 Threaded rod made of V 2A M8 / M6 x 28 mm for fixing push bar P 599 001	•	•	•
	Z 900 943 02 **Z 900 943 64** Aluminium capnut M8, for fixing push bar with Z 908 394	•	•	•

		Door-Series 1.0	RSC without RS	A 72
	**Z 900 939 02** Aluminium door handle 110 x 220 mm	•		•
	Z 911 165 Fixing plate for push grips with 190 mm hole pitch as well as for 150 X 150 mm with 70 mm hole pitch	•		
	Z 905 770 Fixing plate for push grips with 190 mm hole pitch as well as for 150 X 150 mm with 70 mm hole pitch			•
	Z 911 163 Threaded rod made of V2A, M8 x 100, for fixing the supports with door handles or push bars	•		
	Z 900 929 Threaded rod made of V2A, M8 x 85, for fixing the supports with door handles or push bars			•
	Z 906 359 Threaded rod made of V2A, M8 x 20, for fixing with fixing plate Z 911 165	•		•
	**Z 908 873 64** Push grip, aluminium coated, for one-sided and double-sided operation, order 2 for double-sided installation			•
	**Z 908 874 64** Push grip, aluminium coated, for one-sided and double-sided operation, order 2 for double-sided installation			•
	**Z 993 311** Fixing material for push grips, for one-sided installation			•
	**Z 993 312** Fixing material for push grips, for double-sided installation			•